

E HAWK ATV FOR CHILDREN

Electric ATV parameters quote sheet

Our Reps are waiting for you 072 980 5201

Model NUMBER	ATV-LM500	ATV-XGN500	ATV-XLY500	ATV-XGN750	ATV-XBW750	ATV-XZS750	ATV-XZS2	ATV-QY750
Pictures								
Specification of product								
Motor	36V500W	36V500W	48V 500W	60V750W	60V750W	60V750W	60V750W	60V750W
Top speed	15km/h	15KM/H	50 km/h	50km/h	50 km/h	50 km/h	50 km/h	50 km/h
Grade of climb (°)	15	15	30	30	30	30	30	30
Battery	36V 12Ah lead-acid battery	36V 12Ah lead-acid battery	48V 20Ah lead-acid battery	60V 20Ah lead-acid battery	60V 20Ah lead-acid battery	60V 20Ah lead-acid battery	60V 20Ah lead-acid battery	60V 20Ah lead-acid battery
Motor type	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor
Gearing	Chain drive	Chain drive	Shaft drives differential rear axle	Shaft drives differential rear axle	Shaft drives differential rear axle	Shaft drives differential rear axle	Shaft drives differential rear axle	Shaft drives differential rear axle
Braking system	Front and rear disc brakes	Front and rear disc brakes	Front and rear disc brakes	Front and rear disc brakes	Front and rear disc brakes	Front and rear disc brakes	Front and rear disc brakes	Front and rear disc brakes
Gross/net weight (kg)	54/48	94/82	95/85	120/110	120/110	120/110	120/110	130/115
Maximum load (kg)	120	120	120	180	180	180	180	180
Endurance	30 km	28 km	40 km	45 km	45 km	45 km	45 km	45 km
Charging time (Hour)	4-8	4-8	6-8	6-8	6-8	6-8	6-8	6-8
Damping system	Front and rear spring shock absorbers	Front and rear spring shock absorbers	Front and rear hydraulic shock absorbers	Front and rear hydraulic shock absorbers	Front and rear hydraulic shock absorbers	Front and rear hydraulic shock absorbers	Front and rear hydraulic shock absorbers	Front and rear hydraulic shock absorbers
Display			Electronic display	Electronic display	Electronic display	Electronic display	Electronic display	Electronic display
Lights	Headlight, taillight	Headlights, taillights	Headlight, taillight	Headlights, taillights	Headlights, taillights	Headlights, taillights	Headlights, taillights	Headlights, taillights
Gears	D	D/R	3 gear shift +D/R	3 gear shift +D/R	3 gear shift +D/R	3 gear shift +D/R	3 gear shift +D/R	3 gear shift +D/R
Tire size	Front/rear 13 X 5.00-6	Front/back 13 X 5.00-6	Front/rear 16 X 8.00-7	Front18X7-8 / Behind18X9.5-8	Front18X7-8 / Behind18X9.5-8	Front18X7-8 / Behind18X9.5-8	Front18X7-8 / Behind18X9.5-8	Front18X7-8 / Behind18X9.5-8
Wheel hub material	iron	iron	iron	iron	iron	iron	iron	iron
Seat height	850mm	610mm	650mm	700	700	700	700	730
Distance from ground	120mm	120mm	150mm	200mm	200mm	200mm	200mm	200mm
Wheel gauge	880mm	870mm	930mm	950	950	950	950	950
Car dimensions	1100*600*690mm	1450*850*930mm	1380*840*860mm	1450*950*930mm	1550*950*930mm	1450*950*970mm	1450*950*970mm	1500*1000*980mm
Package size	980*580*470mm	1010*610*520mm	1220*600*630mm	1320*820*720mm	1320*760*630mm	1320*720*630mm	1310*760*630mm	1320*760*650mm
Color choice	Red/black/yellow/blue/green/white/army green							
Quantity	108pcs/20ft; 243pcs/40HQ	88pcs/20ft; 230pcs/40HQ	36pcs/20ft; 108pcs/40HQ	48pcs/20ft; 108pcs/40HQ	48pcs/20ft; 108pcs/40HQ	60pcs/20ft; 120pcs/40HQ	48pcs/20ft; 108pcs/40HQ	40pcs/20ft; 100pcs/40HQ