NO	MODEL	Photos	parameter	size	Motor	battery	speed	Mark	Package size
1	BH8 Aluminum alloy frame	de la como	Aluminum alloy frame, tuillight (with steering), free-in-ore switch, single-pash dae brake, 20-40 tire, waterproof line quick release, iron plate crash, Speed, 30-40 Kerner, Starker (Starker, Starker, Starker, Starker, Starker, Gross weight, 55-55G Endurance, 40-60KM Maximum linding ganle, 22° Maximum load: 158KG 4010Q cabinet quantity: 168 units	20"	48V1000W	48V16AH	30- 45KM/H		
2	Dnova Aluminum alloy frame	Broellaholing: 29-67	Alaminum alloy firme, naillight (with storing), three-in-ose switch, single-push of date backs. Thinks time, waterproof line quick release, Net weight 60KG Endmance. 60-75KM Endmance. 60-75KM Maximum linding garde. 33° Maximum linding garde. 33° Maximum linding garde. 33°	13"/14"	52V3000W*2	52V25AH	60- 70KM/H		
3	ZMSUP-01 (iron frame): variable speed model		Ion frame, ion front fork, YL-61F instrument on the left, taillight (with steering), three-sin-one nwitch, stringle-push daise traits, 29×40 Chaoyang tire, Shinman 7- septiment of the string string string string string string string string string string string string string string string string string string string String	20"	48V500W spoke wheel	48V10AH	0.000 (00	If you need to add frame side nets, the cost will increase by S20/vehicle, and the battery net will be \$10 /vehicle	145cm spech
4	ZMSUP-02 (iron frame): variable speed model	12.0	Ion frame, iron front fock, VL-61F instrument on the left, taillight (with steering), three-sin-one writch, single-path disc brails, 20 ⁴⁴ 0.0 Anaryang tire, Shimano 7, week with pame, models from an draw from an experiment of the teleness 3-532 MeVII and the start of the start of the start of the start of the start gross weight: 58AG gross weight: 58AG waiturne: 64-06KM Maximum load: 58AG 40HQ container quantity: 168 units	20"	48V500W spoke wheel	48V10AH	35- 52KM/H	IF add the battery net will be \$10 /vehicle	145cm S ^{ree}
5	ZMSUP-03 (iron frame): variable speed model	6	Inn frame, inon front fork, VL-61F instrument on the left, taillight (with steering), three-sin-one witch, simgle-push dates brake, 20%40 Chaoyang tire, Shimano 7- oegeed, with pump, moleib plone holder, from that rear fenders, 5 wateproof quick releases, inon chainting earth, time: 3-511 Speed: 35-52/XMI Seed: Net weight - 45KG Gaos weight: 3-56KG Maximum load: 15/RSG 48HQ loading quantity: 168 units	20"	48V500W spoke wheel	48V10AH	35- 52KM/H	If you need to add other accessories, the cost will be additional.	145cm 33600
6	ZMSUP-04(iron frame): variable speed model	T	Inn finne, une frun fock, TL-OT moturnest en the left, sulligiet (with atcering), ment with party, mobile phone black, front and rear forkers, T waterproof quick react, with party, mobile phone black, front and rear forkers, T waterproof quick reaces, with charating catals, Seed: 25XM11 Seed: 25XM11 See	20"	48V500W spoke wheel	48V10AH	25KM/H	If you need to add other accessories, the cost will be additional.	140cm 32 ^{cth}
7	ZM25 -Single motor (iron frame): variable speed	000	Into fame, into foot foot, YL-161 Featurement on the left, utilight (with steering), fore-in-one entitely, diag-peads for bracks, 2494 CL Onzyang ture Shimma 7. speed, with pamp, mobile phone holder, front and rear fenders, 5 waterproof quick release, iron charingr granh, Speed. 25XMH Wa weight: 523KG Gross weight: 523KG Gross weight: 523KG Gross weight: 523KG Maximum climbing grade: 25'Maximum load: 150KG 44104 containt- quantity, 216 units	20"	48V500W spoke wheel	48V10AH		With middle basket, but not with battery side net. If battery side net is required, the cost will increase by \$10 /vehicle.	138cm 256%
8	ZM28 (iron frame): variable speed model	6	han dam, inn dont fork 17.441° naturnaren et neb led, direci-nore svikh, tagleg-und dir beich 20/40 Caroyang utt. Sistamo ² -opeot alm pamp, mobile pione holder, front and raar fenders, 5 waterproof quick releases, iron duiring crask, Speed 252KMH Net weight: 47.54G Gross weight: 52.34G Edurance: 0.445KM Maximum clinbag gable: 25° Mattioum hou! 158G	20"	48V500W spoke wheel	48V10AH	25KM/H		150cm 34cm
9	ZM27 (iron frame): Shimano 7-speed		hen dame, joor abcdafe and im log from Gel, YL-6H instances on the left. here:in-nex studie, indigerbal dis britcher, 2014 Ochrospung turk Chiman 7. speed: with pump, mobile phone bolder, front and rear fractors, 5 waterproof quick releases, iron charting crank, charging time 3-5H Speed 2:5-40KMH Net weight: KG Gross weight: KG Endutance: 40-65KM (depending on battery capacity) Maximum climbing: 239 difful container quantity: 168 units	20"	48V500W spoke wheel	48V10AH	25- 40KM/H		145cm 33cm
10	FG-20 (iron frame): Shimano 7-speed	5-0	Into flame, into shoulder and into lac front offset, dures in once writeht single pands for braits, 224/10, downge into, Samona - poped, with pange module phone halder, front and rear fenders, 5 subargoof aprice in the single pand balder, front and rear fenders, 5 subargoof panels, 19, 61 Speed: 25-40KM1 Martinemi climbing; 29 Martinum loads (19 KKG Hallarmen, 40-45KM (depending on hittery capacity)) Martinemi climbing; 29 Martinum loads (19 KKG HallQ) container quantity; 144 units.	20"	48V500W spoke wheel	48V10AH	25- 40KM/H		149cm 3 ^{ACN}
11	ZMDK700 (iron frame): speed change	670	Into finane, iron shoulder and iron teg front field, two-is-noes workh, single path die brake, 24% O. Arooyang tier, Shammo-yroed, with partyn molie phone kalder, front and eur frender, S vanderpool quick releases, non tooth plate crash, charging time. 25% proped 25%MH Macsimum clashing 23% Macsimum clashing 23% MBC or contrast organistics, 26% methy MBC organistics, 20% methy, 26% methy, 26% methy, 26% methy, 26% methy MBC organistics, 20% methy, 26% methy, 2	20"	48V500W spoke wheel	48V10AH	25 KM/H		148cm 3 ⁴⁰⁰
12	DK401	Dido	Model: Dock 011 (cone frame) Tree size 240-64 (cone hack Battery: 481/0 (AH) Moter power: 500W Charging time: 6-8 horns, Speed: 30-47hm ³ New veight: 31kg gross weight: 43.8kg Endurance: 45-60Km, maximum clinibing grade: 25° Maximum load: 150kg, neutriment: 176.1F Using temperature: -10 ⁰ -50 ⁰ Hill(1) loading quartity: 144 unit:	20"	48V500W spoke wheel	48V10AH	30-47km/h		150*34*85cm
13	ZM25-1	ð S	Madel 2025-1 (moi framc), tire size: 20*4.0, color: black Buttery: 40 V (out), durings time: 6-8 hours, weed: 25unh model 25unh maximum (etholog games weight: 6-18 hours, maximum (etholog games 25°), maximum (etholog games 25°), maximum (etholog), instrumet: VLOFF Using temperature: 10°-50° Biol(Q) (obaniq queut): 110 mint	20"	48V500W spoke wheel	48V10AH	25km/h		148*38*96cm
14	ZM25-2	đ	Model 2023-2 (mm frame). trie size 2940, 0.000: Model, hatter; 48V 10.014, motor power: 500W, charging time: 6.8 haure: 118g Gross weight -3.18 kg, endurance: 4.500Kn Maximum (climbing gande 22°, maximum kol: 158g, instrument: 225, operating isompreture: 10°50°,	20"	48V500W spoke wheel	48V10AH	30-47km/h		148*38*96cm

E HAWK Electric Zone is Located in Nairobi Kenya, Our Office Number is 072 98 05201 All of scooters, e bikes and motorcycles are factory made directly. Top Quality UL Listed on all batteries. Nobody can beat us the quality and craftsman ship.

All orders are custom factory direct no middleman. Orders take between 35 to 45 days. A 50% deposit is required not refundable if factory already made scooter.

Our reps can put together any payment plan together for you depending on your income, No one should be without a scooter to get around in Kenya like everyone needs and has a cellphone it's a must have in todays society.